





Order No. 3.68301
Inclined Balancing Beam
 for attachment to Platform 1.50 m

Safety distance 
 Device dimensions 
 Functional distance 



Order No. L3.69350
Vertical Climbing Net
 for attachment to Platform



Scale 1:100

Safety check according to DIN EN 1176

Components

Order No. 3.68301
Inclined Balancing Beam

- 1 Inclined balancing beam
- 1 Stand post with steel foot and chain handrail

Order No. L3.69350
Vertical Climbing Net

- 1 Vertical net with 1 stand post with steel foot
- 1 Bent fireman's pole

Installation information

Surfacing requirements corresponding to a fall height of ≤ 1.50 m (please refer to price list for more detailed information)

Foundations

- Order No. 3.68301**
 1 item 60 x 60 x 50 cm
 Excavation depth 80 cm
- Order No. L3.69350**
 1 item 60 x 60 x 60 cm
 Excavation depth 80 cm
- 1 item 55 x 40 x 30 cm
 Excavation depth 50 cm

Attention:

Exact measurements may vary; for all installation dimensions refer to current assembly instructions.
 Technical changes reserved.

Technical information

Equipment made of mountain larch

Order No. 3.68301

Peeled white

Palisades peeled white means that bark, cambium and sapwood are removed, the natural shape of the trunk is preserved and can be experienced



Bevel cut

Vertical stand posts with bevelled end grain section as constructive wood preservation measure



Ground anchor

All parts used for anchoring to the ground are made of hot-dip galvanised steel or stainless steel



Chains

Chains made of hot-dip galvanized steel (1.4301 / 1.4571 at extra charge) welded before galvanising, short-linked, without eyelets on the connecting parts, easy to exchange and shorten



Order No. L3.69350

Peeled white

Palisades peeled white means that bark, cambium and sapwood are removed, the natural shape of the trunk is preserved and can be experienced



Richter Hercules type rope

Richter Hercules type rope, a combination of galvanised six-strand steel cables and polyester yarn, diameter > 20 mm, laid and glued with very good abrasion resistance, strong sheathing even in the case of damage by puncturing



Aluminium rope pressing

Aluminium rope pressing, cylindrically pressed, with rounded ends



S-connectors

S-connectors $\varnothing 8.1$ mm, made of high-quality stainless steel, rounded



Ground anchor

All parts used for anchoring to the ground are made of hot-dip galvanised steel or stainless steel




For more detailed explanation of the quality characteristics see price list.

Firemen's pole of stainless steel, glass bead blasted, $\varnothing 42$ mm

Dimensions

(small deviations possible)

Order No. 3.68301	
Length	3.00 m
Weight	100 kg
Order No. L3.69350	
Height of net	2.00 m
Net size	1.75 x 2.50 m
Weight	70 kg



3.68301




L3.69350

Order No. 3.67499

Inclined Wall



for attachment to Platform 2.00 m



Order No. 3.69440

Holding Rope


for Inclined Wall,
installation height 2.00 m



Order No. 3.67522

Inclined Wall



for attachment to Platform 1.50 m



Order No. 3.69470

Holding Rope

for Inclined Wall,
installation height 1.50 m



Scale 1:100

Safety check according to DIN EN 1176

Attention:
Exact measurements may vary;
for all installation dimensions refer
to current assembly instructions.

Technical changes reserved.



3.67499



3.67522



3.69440 / 3.69470

Technical information

Order No. 3.67499 / 3.67522

Equipment made of non-impregnated mountain larch

Core-free

Sawn-timbers core-free, thus decreasing occurrences of cracking and undesired changes in shape



Tongue and groove

Tongue and groove planks made of 4 cm solid wood, highly resilient, no trickling of dust / sand, protection against direct rain



Ground anchor

All parts used for anchoring to the ground are made of hot-dip galvanised steel or stainless steel



Order No. 3.69440 / 3.69470

Richter Hercules type rope

Richter Hercules type rope, a combination of galvanised six-strand steel cables and polyester yarn, diameter > 20 mm, laid and glued with very good abrasion resistance, strong sheathing even in the case of damage by puncturing



Aluminium rope pressing

Aluminium rope pressing, cylindrically pressed, with rounded ends



Rotating rope connection

Rotatable fitting without dangerous openings, with sintered bush with integrated swivel to ensure the rope untwists



For more detailed explanation of the quality characteristics see price list.

Standard colour rope: rainbow

Dimensions

(small deviations possible)

Order No. 3.67499

Installation height	2.00 m
Length	2.90 m
Width	2.00 m
Weight	200 kg

Order No. 3.67522

Installation height	1.50 m
Length	2.20 m
Width	2.00 m
Weight	150 kg

Components

1 Inclined wall with inclination 45°
and 2 steel feet

Installation information

Surfacing requirements corresponding to a fall height of

Order No. 3.67499 ≤ 2.00 m

Order No. 3.67522 ≤ 1.50 m

(please refer to price list for more detailed information)

Foundations

Order No. 3.67499 / 3.67522

2 items 50 x 50 x 40 cm

Excavation depth 60 cm