

Play value

The tall slender stork invites role play as well as lively spinning fun. A child can sit on it and snuggle up against it, while fellow playmates can stand on the turntable and thus enjoy the movement as well. Its aesthetic shape gives the play space a special character.

Fundamental characteristics

- Child proportions according to ergonomic requirements
- Natural wooden surface which appeals to the senses
- Turning movement
- Incentive for playing: role-playing games
- Movement: riding, moving one's centre of gravity

Recommended for



- Kindergarten children
- Supervised play areas, such as kindergartens, schools, after-school programmes or similar
- Public play areas without supervision, such as playgrounds, parks or similar



Rotating Stork



Order No. 4.24283
Rotating Stork



Safety distance →
Device dimensions —●—
Functional distance —|—

Scale 1:100

Safety check according to DIN EN 1176

Components

- 1 Stork
- 1 Foundation frame

Installation information

Surfacing requirements corresponding to a fall height of ≤ 0.60 m (please refer to price list for more detailed information)

Foundations
1 item 60 x 60 x 20 cm
Excavation depth 60 cm

Attention:
Exact measurements may vary;
for all installation dimensions refer
to current assembly instructions.
Technical changes reserved.

Technical information

Equipment made of non-impregnated mountain larch, Inner frame made of stainless steel, glass bead blasted

Peeled white

Palisades peeled white means that bark, cambium and sapwood are removed, the natural shape of the trunk is preserved and can be experienced



Plywood

Plywood made of mountain larch, three-layer (3 cm) or five-layer (4 cm). High dimensional stability, waterproof, glued according to DIN EN 13353:2011



Richter Hercules type rope

Richter Hercules type rope, a combination of galvanised six-strand steel cables and polyester yarn, diameter > 20 mm, laid and glued with very good abrasion resistance, strong sheathing even in the case of damage by puncturing



Aluminium rope pressing

Aluminium rope pressing, cylindrically pressed, with rounded ends



Ground anchor

All parts used for anchoring to the ground are made of hot-dip galvanised steel or stainless steel



Roller bearings

High-quality roller bearings made of chrome steel or stainless steel for rotating elements, easy to maintain and exchange, sealed



For more detailed explanation of the quality characteristics see price list.

Sturdy, welded substructure, painted

Surfacing made of checker plate

Foundation frame made of steel

Dimensions

(small deviations possible)

Height	1.40 m
Diameter	0.50 m
Weight	60 kg
with Foundation frame	70 kg

