

# Instructions for wear checks of play equipment

The equipment must be checked for correct operation and safety, especially the points listed below:

Proof of maintenance

Playground.....

Date of installation .....


Checks depend on the type of equipment. Any equipment with moving parts must be checked at least twice a year, static equipment at least once a year.

Intervals for maintenance work and checks generally depend on

- location
- usage
- frequency of use
- possible vandalism

For more details see also our general instructions for maintenance of playgrounds!

**Large Excavator**  
**Order No. 5.30000**



## Joins

1. Check that swivel joint moves smoothly (remove sand which has accumulated around the support foot).
2. Check that main joint moves smoothly.
3. Check that the joints of the excavator arm and excavator bucket move smoothly.
4. Apply grease to the lubricating nipple on the bucket joint.

## Brake

5. Perform operational test: when load is placed on the seat, it should be possible to turn the platform; with no load placed on the seat, any turning movement should stop immediately. Replace rubber buffer if worn down.

## Excavator bucket

6. File down any sharp edges on the shovel caused by wear and tear.

## Seat

7. Check condition of seat surface, smooth if necessary.

## Lubrication

8. If necessary, lubricated with suitable grease (universal grease)

## Structural stability

9. Check anchoring to the ground once a year.

Special notes, e.g. for repairs

Repair not carried out, it is still possible to play on equipment


Repair not carried out, equipment is taken out of action

All work carried out, everything is in order

Maintenance carried out by:

..... Date .....

**Spare parts**  
**Large Excavator**  
**Order No. 5.30000**




Please note that the safety standards of the equipment must not be affected. Therefore, when carrying out repairs it is helpful to **only use original parts**.

**Order No. Spare parts**


**0.88180 Set of brass bushes**



**99.00660 Seat**



**0.70250 Foundation frame**



**0.88181 Rubber buffer**

