

Instructions for wear checks of play equipment

The equipment must be checked for correct operation and safety, especially the points listed below:

Proof of maintenance

Playground

Date of installation


Checks depend on the type of equipment. Any equipment with moving parts must be checked at least twice a year, static equipment at least once a year.

Intervals for maintenance work and checks generally depend on

- location
- kind of use
- frequency of use
- possible vandalism

For more details see also "General instructions for maintenance of playgrounds".

Roundabout
Order No. 6.26000




Operation

1. Check that roundabout moves smoothly, check bearings for wear and tear.
2. Check that moulded dish is securely connected, re-tighten bolts if necessary.

Structural stability

3. Examine load-bearing parts for corrosion (remove the moulded dish) once a year.

	Note: Safety according to the standard for Playground Equipment 1176-5:2008; 5.2.3.
	The distance between the roundabout and the ground must be at least 6 cm but must not exceed 11 cm.
Crushing hazard	



Special notes, e.g. for repairs

Repair not carried out, it is still possible to play on equipment

Repair not carried out, equipment is taken out of action


All work carried out, everything is in order

Maintenance carried out by:

For spare parts refer to back of page.

..... Date

**Spare Parts
Roundabout
Order No. 6.26000**




Please note that the safety standards of the equipment must not be affected. Therefore, when carrying out repairs it is helpful to **only use original parts.**

Order No. Spare part

0.20000 bolt and washer



0.20001 moulded dish for roundabout without bolts



0.70200 foundation frame

