



**Order No. 3.66055**  
**Support Frame for Suspension Bridge**  
**Order No. 3.66645**  
**Support Frame for Rope Bridge**  
 Installation height 1.50 m

Safety distance   
 Device dimensions   
 Functional distance 



**Order No. 3.66057**  
**Support Frame for Suspension Bridge**  
**Order No. 3.66647**  
**Support Frame for Rope Bridge**  
 Installation height 1.00 m



Scale 1:100

Safety check according to DIN EN 1176

**Components**

1 Frame each

**Installation information**

Surfacing requirements corresponding to a fall height determined by installation height (please refer to price list for more detailed information)

Foundations  
 1 item 60 x 60 x 40 cm  
 Excavation depth 60 cm

**Attention:**  
**Exact measurements may vary;**  
**for all installation dimensions refer to current assembly instructions.**  
 Technical changes reserved.

**Technical information**

All Support Frames made of non-impregnated mountain larch

**Core-free**

Sawn-timbers core-free, thus decreasing occurrences of cracking and undesired changes in shape



**Profiled washer**

Profiled washer for covering protruding screw heads according to standard, improved pressure distribution and protection against water. Impedes loosening the bolt



**Ground anchor**

All parts used for anchoring to the ground are made of hot-dip galvanised steel or stainless steel



**For more detailed explanation of the quality characteristics see price list.**

Metal braces hot-dip galvanised, Ø 83 mm




3.66055 / 3.66645




3.66057 / 3.66647



**Order No. 3.66290**  
**Support Frame for Chain Path**  
 Installation height 1.50 / 1.00 m



Safety distance →  
 Device dimensions —●—  
 Functional distance —|—



**Order No. 3.66360 / 3.66367**  
**Support Frame for Bridge**  
 Installation height 1.50 / 1.00 m



Scale 1:100

Safety check according to DIN EN 1176

**Technical information**

All Support Frames made of non-impregnated mountain larch

**Core-free**

Sawn-timbers core-free, thus decreasing occurrences of cracking and undesired changes in shape



**For more detailed explanation of the quality characteristics see price list.**

**Components**

1 Frame each

**Installation information**

Surfacing requirements corresponding to a fall height determined by installation height (please refer to price list for more detailed information)

**Attention:**

**Exact measurements may vary; for all installation dimensions refer to current assembly instructions.**

Technical changes reserved.



3.66290



3.66360



3.66367