





**Order No. L3.68500  
Double Hanging Rope**



Safety distance   
 Device dimensions   
 Functional distance 



**Order No. L3.69010  
Balancing Rope with Holding Rope**



Scale 1:100

Safety check according to DIN EN 1176

**Components**

**Order No L3.68500  
Double Hanging Rope**  
 4 Stand posts with steel feet  
 2 Ropes

**Order No L3.69010  
Balancing Rope with Holding Rope**  
 1 Stand post with steel foot  
 2 Ropes

**Installation information**

Surfacing requirements corresponding to a fall height of  
**Order No L3.68500** ≤ 2.00 m  
**Order No L3.69010** ≤ 0.60 m  
 (please refer to price list for more detailed information)

Foundations  
**Order No L3.68500  
Double Hanging Rope**  
 2 items 110 x 60 x 60 cm  
 Excavation depth 80 cm  
**Order No L3.69010  
Balancing Rope with Holding Rope**  
 1 item 60 x 60 x 60 cm  
 Excavation depth 80 cm

**Attention:**  
**Exact measurements may vary;**  
**for all installation dimensions refer**  
**to current assembly instructions.**  
 Technical changes reserved.

**Technical information**

Equipment made of non-impregnated mountain larch

**Peeled white**  
 Palisades peeled white means that bark, cambium and sapwood are removed, the natural shape of the trunk is preserved and can be experienced



**Bevel cut**  
 Vertical stand posts with bevelled end grain section as constructive wood preservation measure



**Richter Hercules type rope**  
 Richter Hercules type rope, a combination of galvanised six-strand steel cables and polyester yarn, diameter > 20 mm, laid and glued with very good abrasion resistance, strong sheathing even in the case of damage by puncturing



**Aluminium rope pressing**  
 Aluminium rope pressing, cylindrically pressed, with rounded ends



**Rope connection fixed**  
 Fixed rope connection without dangerous openings. Screw connection adjustable and countersunk in the wood



**Ground anchor**  
 All parts used for anchoring to the ground are made of hot-dip galvanised steel or stainless steel




**For more detailed explanation of the quality characteristics see price list.**


**Dimensions**  
 (small deviations possible)

<b>Order No. L3.68500 Double Hanging Rope</b>	
Height of rope	2.00 m
Length	3.25 m
Width	0.55 m
Weight	180 kg

<b>Order No. L3.69010 Balancing Rope with Holding Rope</b>	
Height of balancing rope	0.40 m
Height of holding rope	1.40 m
Length	3.05 m
Weight	50 kg



L3.68500




L3.69010

**Order No. 3.69502**

**Climbing Trunk**

for attachment on Square Tower  
with Roof 2.00 m (**Order No. L3.20600**)  
Installation height 1.00 m




Safety distance →  
Device dimensions —●—  
Functional distance —|—

**Order No. 3.69511**

**Climbing Trunk with handrail on one side**


for attachment on Square Tower 1.50 m (**Order No. L3.20500**)



**Order No. 3.69521**

**Climbing Trunk with double-sided handrail**

for attachment on Square Tower  
with Roof 2.00 m (**Order No. L3.20600**)



Scale 1:100

Safety check according to DIN EN 1176

**Technical information**

Equipment made of non-impregnated mountain larch

**Peeled white**

Palisades peeled white means that bark, cambium and sapwood are removed, the natural shape of the trunk is preserved and can be experienced



**Bevel cut**

Vertical stand posts with bevelled end grain section as constructive wood preservation measure



**Ground anchor**

All parts used for anchoring to the ground are made of hot-dip galvanised steel or stainless steel



**Chains**

Chains made of hot-dip galvanized steel (1.4301 / 1.4571 at extra charge) welded before galvanising, short-linked, without eyelets on the connecting parts, easy to exchange and shorten



**For more detailed explanation of the quality characteristics see price list.**

**Dimensions**

(small deviations possible)

<b>Order No. 3.69502</b>	
Length	1.75 m
Weight	50 kg
<b>Order No. 3.69511</b>	
Length	2.35 m
Weight	100 kg
<b>Order No. 3.69521</b>	
Length	3.15 m
Weight	140 kg

**Components**

**Order No. 3.69502**  
1 Climbing trunk with steel foot

**Order No. 3.69511**  
1 Climbing trunk  
1 Stand post with steel foot and chain handrail

**Order No. 3.69521**  
1 Climbing trunk  
2 Stand posts with steel feet and chain handrails

**Installation information**

Surfacing requirements corresponding to a fall height determined by installation height (please refer to price list for more detailed information)

**Foundations**

**Order No. 3.69502**  
1 item 40 x 40 x 20 cm  
Excavation depth 40 cm

**Order No. 3.69511**  
1 item 60 x 60 x 60 cm  
Excavation depth 80 cm

**Order No. 3.69521**  
2 items 60 x 60 x 60 cm  
Excavation depth 80 cm

**Attention:**

**Exact measurements may vary; for all installation dimensions refer to current assembly instructions.**

Technical changes reserved.



3.69502



3.69511



3.69521