## **Play value**

Climbing Structures made from hand-processed irregular round logs, can be integrated into a strongly nature-oriented environment due to their formal expressive character. Many children can play within a small space; Climbing Structures can even absorb the arrival of a large number of children who wish to play on it and incorporate all of them within a flowing play rhythm. Climbing Structures do not only allow for climbing, experiencing height, and for having a sensual experience with hands and feet, but they can also be used as a nice seat for relaxing and observing.





**Climbing Structure 21** 

## **Fundamental characteristics**

- Natural, strong posts
- No pre-determined play procedures, individual mastering
- Incentive for playing: strong, challenging structure
- Movement: climbing, balancing, doing exercise

# **Recommended for**

- Kindergarten children
- School children
- Supervised play areas, such as kindergartens, schools, after-school programmes or similar
- Public play areas without supervision, such as playgrounds, parks or similar





Order No. 6.51021 / L6.51021 Climbing Structure 21 Safety distance

Device dimensions

Functional distance

## **Height details in meters**





Scale 1:200

Safety check according to DIN EN 1176 and "safety in another way"

## **Components**

8 Stand posts 12 Connecting tie beams Fittings

## **Dimensions**

(small deviations possible)

 Length
 8.20 m

 Width
 4.50 m

## Installation information

Surfacing requirements corresponding to a fall height of  $\leq$  0.60 m (please refer to price list for more detailed information)

Foundations 8 items 80 x 80 x 60 cm Excavation depth 80 cm

## Vote

The climbing structure is an individual construction which is only partly pre-assembled in our workshop. Therefore, the installation needs to be carried out by an installation company authorised by us. Technical changes reserved. Equipment also available for environmental friendly foundations (Order No. G6.51021).

#### **Technical information**

Posts made of robinia, Ø 15 - 21 cm

#### **Peeled white**

Palisades peeled white means that bark, cambium and sapwood are removed, the natural shape of the trunk is preserved and can be experienced



## **Bevel cut**

Vertical stand posts with bevelled end grain section as constructive wood preservation measure



## **Profiled washer**

Profiled washer for covering protruding screw heads according to standard, improved pressure distribution and protection against water. Impedes loosening the bolt



## Adjustable

Adjustable two-piece bolt connection, easy to maintain, no projecting threads



## **Distance fitting**

Screw connection with distance fitting to avoid entrapment areas



## Order No. L6.51021

As above, but de-barked posts made of non-impregnated mountain larch with steel feet, Ø 15 - 21 cm, splinter free

## **Ground anchor**

All parts used for anchoring to the ground are made of hot-dip galvanised steel or stainless steel



# Relief cut

Targeted relief cut as an effective measure against cracks caused by drying. The cut defines the position of the stress equalization in the trunk and minimises natural cracking



For more detailed explanation of the quality characteristics see price list.

