| This copy may be copied for maintenance of Richter pla | y equipment. | Page 1 |
|--|---|---------------------------------|
| Instructions for wear checks of play equipment | The equipment must be checked for correct operation and safety, especially the points listed below: | Proof of maintenance |
| Playground | Wooden parts | |
| Date of installation Equipment-specific inspections must be | Check for rot and, if necessary, smooth out splinters and round off sharp edges of cracks. | |
| carried out at least twice a year. Intervals for maintenance work and checks generally depend on | 2. Check that all bolts and screws are tight and retighten if necessary. | |
| the location the usage the frequency of use | Check the ash wood rungs of the ladders for wear and tear, the remaining diameter must be at least 30 mm. | |
| possible vandalism For more details see also our general | 4. Recommendation: apply paraffin wax to the upper end grain areas once a year, please refer to Order No. 0.90100, 1 litre. | |
| instructions for maintenance of playgrounds! | Structural stability | |
| Play Village | In order to check for rot at wooden parts and steel feet for corrosion, uncover the foundations once a year. | |
| Order No. 2.15000 | Combination equipment | |
| | Please pay attention to the separate main- tenance notes for the following combination equipment:Rope Bridge 3 m3.66550Single Swing special3.19802Sand Play Equipment3.19100Small Children Slide3.19200Slide, width 0.45 m3.19210Fastening Frame for Chain Path3.66290Rope Bridge Frame3.66645Running Boards for3.66090Suspension Bridge 3 m3.66055Bridge 3 m3.66320Running Board Timbers3.66263for Chain Path3.66263for Chain Path3.66263Running Board Timbers3.66263for Chain Path3.66263Repair not carried out,8 | Special notes, e.g. for repairs |
| | it is still possible to play on equipment | |
| | Repair not carried out, equipment is taken out of action | |
| | All work carried out, everything is in order | |
| | Maintenance carried out by: | |
| | Date | |