Instructions for wear checks of play equipment

Playground.....

Date of installation


Checks depend on the type of equipment. Any equipment with moving parts must be checked at least twice a year, static equipment at least once a year.

Intervals for maintenance work and checks generally depend on

- the location
- the usage
- the frequency of use
- possible vandalism

For more details see also "General instructions for maintenance of playgrounds".

Splash Hopper for external sprayhead Order No. 5.25070



The equipment must be checked for
correct operation, especially the points
listed below:

Lubrication

 The plastic piston needs to be regularly lubricated with special fitting grease. The intervals will depend on how intensively the equipment is used. To do so, the moveable stand cylinder must be lifted using the supplied metal handles. Carefully push them along the cylinder, past the cover seal, into the concrete housing and hook onto the bottom edge. Lift up the stand cylinder a little bit at first and unscrew the lock nut. Then remove the whole cylinder. Attention: Do not put your hand under the lower edge – danger of getting squashed!

Disassembly

- 2. The equipment must be disassembled during sub-zero conditions as follows:
 - a. Disconnect from the water mains and disassemble the stand cylinder as described in point **1**.
 - b. Remove the summer lid.c. Loosen the hose connector on the jet
 - connection and drain the jet line.d. Loosen the plastic nuts on the base.
 - e. Loosen the hose connector of the water reservoir connection.
 - f. Loosen the screw connections of the water reservoir.
 - g. Take out the equipment and water reservoir.
 - h. Remove sand deposits from the trap as well as from the bottom of the concrete housing.
 - i. Replace the trap (pin must point upward).
 - j. Close the concrete housing with the winter lid.

		Sp	
Repair not carried out, it is still possible to play on equipment			
Repair not carried out, equipment is taken out of action			
All work carried out, everything is in order			
Maintenance carried out by:			
Date			

Proof of maintenance

cial notes, e.g. for repairs