Instructions for wear checks of play equipment

Playground.....

Date of installation

Checks depend on the type of equipment. Any equipment with moving parts must be checked at least twice a year, static equipment at least once a year.

Intervals for maintenance work and checks generally depend on

- the location
- the usage
- the frequency of use
- possible vandalism

For more details see also "General instructions for maintenance of playgrounds".	4.	Check the bearing for proper operation.			
		Rubber			
Turning Tyre Order No. 6.27000/6.27005	5.	Check tyres for wear and tear as well as for vandalism; replace if required.]	
					Special notes, e.g. for repairs
		pair not carried out, s still possible to play on equipment]	
		pair not carried out, uipment is taken out of action]	
		work carried out, erything is in order]	
	Ма	intenance carried out by:	I		
For spare parts refer to back of page.	Date				

Proof of

maintenance

The equipment must be checked for correct operation and safety, especially the points listed below:

Structural stability

- 1. Uncover the foundation once a year in order to check the structural stability as follows: - steel for corrosion
 - anchoring to the ground for stability
 - condition of concrete foundation
- 2. Check that the board is securely connected to the tyre, retighten screws if necessary.

Metal/fittings

3. Check that the spring fitting is securely connected and retighten bolts/screws if necessary.

Spare parts Turning Tyre Order No. 6.27000/6.27005



Please note that the safety standards of the equipment must not be affected. Therefore, when carrying out repairs it is helpful to **only use original parts**.

Order No. Spare part	
0.92451 compression spring	
0.92480 clamping block	
0.92481 used tyre	
0.70300 foundation anchor	
0.70310 bearing	Note This list includes only the spare parts ordered most frequently. Other spare parts on request.