Instructions for wear checks of play quipment	The equipment must be checked for correct operation and safety, especially the points listed below:	Proof of maintenance
Playground	Concrete	
Date of installation Checks depend on the type of equipment. Any equipment with moving parts must be checked at least twice a year, static	 Check for vandalism (chipped edges), and if necessary deburr sharp edges with an angle grinder or mend them with fast drying concrete or epoxy resin. 	
equipment at least once a year.	Ropes and nets	
Intervals for maintenance work and checks generally depend on - location	 Check the connections of rope and net elements for damage and ensure they are tight, retighten if necessary. 	
 usage frequency of use possible vandalism For more details see also "General	 Check plastic sleeves of rope and net elements for wear and tear; replace any elements whose inner steel strands are damaged. 	
instructions for maintenance of playgrounds".	Whisk and firemen's pole	
Rope Course Type 02 Order No. 6.49020	 Check the connections to the concrete column and retighten if necessary. 	
	Whisk: Ensure that the whisk rotates smoothly(brass bushes).	
	 Check weld seams for strength (cracks), if necessary re-weld and grind down in a competent manner. 	
	Structural stability	
	 Have trained personnel check the condition of the concrete columns twice a year. Dig around the columns down to the foundation before carrying out this step. 	for repairs
Attention: Strictly adhere to the		Special notes, e.g. for repairs
A maintenance intervals!	Repair not carried out, it is still possible to play on equipment	
	Repair not carried out, equipment is taken out of action	
	All work carried out, everything is in order	
	Maintenance carried out by:	