| Instructions for wear checks of play equipment | The equipment must be checked for correct operation and safety, especially the points listed below: | Proof of maintenance |
|---|---|---------------------------------|
| Playground | Wooden parts | |
| Date of installation Checks depend on the type of equipment. | Check for rot and, if necessary, smooth out splinters and round off sharp edges of cracks. | |
| Any equipment with moving parts must be checked at least twice a year, static equipment at least once a year. | Check that all bolts and screws are tight and retighten if necessary. | |
| Intervals for maintenance work and checks generally depend on | Check the ash wood rungs of the ladders for wear and tear, the remaining diameter must be at least 30 mm. | |
| locationusagefrequency of usepossible vandalism | 4. Recommendation: apply paraffin wax to the upper end grain areas once a year, please refer to Order No. 0.90100, 1 litre. | |
| For more details see also our general | Flag | |
| instructions for maintenance of playgrounds! | Check flag for tight fit, retighten if necessary. | |
| | 6. Check for damage. | |
| Castle Tower Order No. 3.22000 | 7. For turnable flag: Check movable parts for smooth running, clean if necessary. | |
| 6 5 | Window | |
| | Make sure that the rope nets are securely connected and check for wear and tear. | |
| | Structural stability | |
| 7 | 9. In order to check for rot at wooden parts and steel feet for corrosion, uncover the foundations once a year. Output Description: | Special notes, e.g. for repairs |
| | Repair not carried out, it is still possible to play on equipment | |
| | Repair not carried out, equipment is taken out of action | |
| 8 | All work carried out, everything is in order | |
| | Maintenance carried out by: | |
| | Date | ; |